


PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: H04R 1/10	A1	(11) International Publication Number: WO 98/47311 (43) International Publication Date: 22 October 1998 (22.10.98)
(21) International Application Number: PCT/US98/07680 (22) International Filing Date: 17 April 1998 (17.04.98) (30) Priority Data: 08/837,440 17 April 1997 (17.04.97) US (71) Applicant: MINNESOTA MINING AND MANUFACTURING COMPANY [US/US]; 3M Center, P.O. Box 33427, Saint Paul, MN 55133-3427 (US). (72) Inventors: HALL, Ronald, W.; P.O. Box 33427, Saint Paul, MN 55133-3427 (US). TAYLOR, Harry, B.; P.O. Box 33427, Saint Paul, MN 55133-3427 (US). (74) Agents: BUCKINGHAM, Stephen, W. et al.; Minnesota Mining and Manufacturing Company, Office of Intellectual Property Counsel, P.O. Box 33427, Saint Paul, MN 55133-3427 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: HEADSET ASSEMBLY**(57) Abstract**

An ergonomic headset assembly having increased comfort and convenience of use is provided. In accordance with one embodiment of the invention, a headset assembly is provided which includes a first headpiece pivotally coupled to a second flexible headpiece. The headset assembly further includes means for limiting the pivotal movement of the flexible headpiece with respect to the first headpiece. This allows the tension of the headset assembly to be suitably adjusted to the head size of the wearer. In accordance with another embodiment of the invention, a headset assembly which includes a headband and an electronics housing pivotally coupled to the headpiece is provided. The pivotal coupling of the electronics housing with respect to the headband allows the electronics housing to be swung away from a user's ear and provides additional comfort to the user. In accordance with yet another embodiment of the invention, a headset assembly having an electronics housing coupled to a clip member is provided. The clip member allows the electronics housing to be removably coupled between a headband and a hat of a user.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

HEADSET ASSEMBLY

5

Field of the Invention

The present invention relates generally to headset assemblies and, more particularly, to a headset assembly having improved ergonomics.

Background of the Invention

10

Headset assemblies are frequently used in a wide variety of applications and across a broad range of industries. For example, in the fast food industry, one or more employees at drive-through fast food restaurants typically wear a headset assembly to receive orders from patrons in the drive-through lane. Similarly, in the banking industry, tellers at banks having drive-through lanes may wear headset assemblies to communicate with customers. In the retail industry, headsets are commonly used by stockroom and other employees to communicate with one another within a large area, such as a department store or a warehouse.

15

A typical headset assembly includes a headband and an electronics housing. The headband typically consists of one single-rate leaf spring having only one unstressed width, but which is flexed to fit different sized heads. The electronics housing is typically attached to one end of the headband and usually includes an earphone speaker, a microphone boom, and the electronic circuitry necessary to operate the earphone and microphone. While being commonplace in today's society, conventional headsets are extremely uncomfortable and inconvenient to use.

20

25

Summary of the Invention

Generally the present invention relates to a headset assembly having increased comfort and convenience of use. In accordance with one embodiment of the invention, a headset assembly is provided which includes a first headpiece pivotally coupled to a second flexible headpiece. The headset assembly further includes means for limiting the pivotal movement of the flexible headpiece with

30

respect to the first headpiece. This allows the tension of the headset assembly to be suitable adjusted to the head size of the wearer.

5 In accordance with another embodiment of the invention, a headset assembly which includes a headband and an electronics housing pivotally coupled to the headpiece is provided. The pivotal coupling of the electronics housing with respect to the headband allows the electronics housing to be swung away from a user's ear and provides additional comfort to the user.

10 In accordance with yet another embodiment of the invention, there is provided a headset assembly having an electronics housing removably coupled to a headband. The electronics housing may, for example, be removably coupled between a headband and a cap of a user. The headset assembly may include a clip member for removably coupling the headband to the electronics housing.

15 The above summary of the present invention is not intended to describe each illustrated embodiment. The figures and the detailed description which follow more particularly exemplify these embodiments.

Brief Description of the Drawings

20 The invention may be more completely understood in consideration of the following detailed description of various embodiments of the invention in connection with the accompanying drawings, in which:

Figure 1 is a perspective view of an exemplary headset assembly in accordance with one embodiment of the present invention;

Figures 2A and 2B are front cross sectional views of the headset assembly of Figure 1;

25 Figures 3-5 are front plan views of the exemplary headset assembly of Figure 1 shown at different width settings;

Figure 6 is a front plan view of an exemplary clip member coupled to an electronic housing in accordance with one embodiment of the present invention;

30 Figures 7A-7B are views of an exemplary adapter in accordance with one embodiment of the invention;

Figure 8 is a front plan view of the exemplary headset assembly of Figure 1;
and

Figure 9 is an exploded perspective view of the headset assembly of
Figure 1.

5 While the invention is amenable to various modifications and alternative
forms, specifics thereof have been shown by way of example in the drawings and
will be described in detail. It should be understood, however, that the intention is
not to limit the invention to the particular embodiments described. on the contrary,
the intention is to cover all modifications, equivalents, and alternatives falling within
10 the spirit and scope of the invention as defined by the appended claims.

Detailed Description of the Drawings

 The present invention generally relates to headset assemblies having one or
more ergonomic features which increase the comfort and convenience of the
15 headset assembly for a user. An appreciation of various aspects and features of the
invention will be gained through a discussion of an exemplary embodiment. While
the exemplary embodiment illustrates a headset assembly which incorporates a
number of these features, the present invention is not so limited. Headset
assemblies including any one or combination of the features are intended to be
20 covered by the present invention.

 Figures 1 and 2A-2B are perspective and cross-sectional views of an
exemplary headset assembly in accordance with one embodiment of the invention.
The headset assembly 100 includes a headband 110 and an electronics housing 120.
The electronics housing 120 generally encloses headset electronics, such as a circuit
25 board, battery, etc. Mounted on the housing may, for example, be an earphone
speaker 128, a microphone boom 126, and a touchpad 124 for operating the
headset electronics. As should be appreciated, the earphone speaker 128 and
microphone boom 126 are typically pivotally mounted to the housing 120 to
facilitate comfortable positioning. Inwardly facing pads 130 formed, for example,
30 from a polyethylene foam, may be mounted on the headset assembly 100. As will
be discussed more fully below, a battery 900 is provided on the housing 120 as well.

As noted above, the exemplary headset assembly 100 illustrates a number of features which enhance the convenience and comfort for a user. The exemplary headband 110 advantageously allows a user to adjust the unstressed width of the headband. The headband 110 generally includes two headpieces 112 and 114, pivotally connected to one another, and a mechanism for limiting the pivotal movement of the headpieces so that the unstressed width of the headband 110 may be adjusted. At least one of the headpieces is relatively flexible so as to provide tension against the head of a user and thereby hold the headset in place.

In the illustrated embodiment, the two headpieces 112 and 114 include a relatively flexible headpiece 114 and a relatively rigid support headpiece 112. The support headpiece 112 generally provides a supporting structure against which the flexible headpiece 114 may bend so as to provide the desired head tension to keep the headset in place. The headpieces 112 and 114 may be made of a number of different materials. For example, the flexible headpiece 114 may be formed from a flexible plastic while the support headpiece 112 may be formed from a relatively more rigid plastic material. One suitable plastic is Nylon, for example.

The flexible headpiece 114 is pivotally coupled to the support headpiece 112 near the end of the support headpiece 112 using a pin 117. However the invention is not so limited. The pivotally connection may be formed in other manners. For example, the two headpieces 112 and 114 may be integrally formed with a relatively thin portion forming an integral hinge between the two headpieces.

In the exemplary embodiment, the mechanism for limiting the pivotal movement of the flexible headpiece 114 with respect to the support headpiece 112 includes a tab 162 slidably mounted on a portion 164 of the support headpiece 112, as best shown in Figure 2B. In general, as the tab 162 is moved outwardly and inwardly, the unstressed width of the headband increases and decreases, respectively. In this manner, the unstressed width of the headband 110 may be appropriately adjusted to comfortably fit a user's head.

As best shown in Figures 2A and 2B, the tab 162 includes a surface 166 which engages the flexible headpiece 114 to both limit the pivotal movement of the flexible headpiece 114 as well as provide a structure against which the flexible

headpiece 114 may flex or bend to provide head tension. The flexible headpiece 114 can be pivotally moved until it contacts the surface 166 at which point further movement of the flexible headpiece 114 results in the creation of a tensile force from the headpiece 114.

5 As best illustrated in Figure 2B, the exemplary tab 162 includes an upper portion 165 and a lower portion 167, mounted to the extended portion 164 of the support headpiece 112 using a pin 169. The tab 162 includes a set of groves 168a which mate with a set of groves 168b on a surface of the headpiece portion 164 for setting the position of the tab 162 (and the width of the headband 100)- A leaf
10 spring 169 may be provided to bias the groove sets 168a and 168b against one another. The leaf spring bias generally allows the tab to be readily repositioned yet prevents the tab from slipping on the headpiece portion 164 when pressure from the flexible headpiece is applied.

 It should be appreciated that the tab 162 is provided by way of example
15 only. A wide variety of other structures and mechanisms may be used to limit the pivotal movement of the flexible headpiece 114. For example, a mechanism having a surface which is moved in a different plane than that of tab surface 166 may be used. Moreover, the present invention is not limited to three or any other fixed number of unstressed widths.

20 As illustrated in Figures 3-5, in the exemplary embodiment, the tab 162 is configured to allow pivotal movement of the flexible headpiece 114 to three different widths. More particularly, Figure 3 illustrates the tab 162 at an inner most position, which allows the flexible headpiece to pivotally move outward to an unstressed width W1. This provides the narrowest headband unstressed width and
25 would be suitable for users having smaller head sizes. Figure 4 shows the tab 162 at an intermediate position, which allows the flexible headpiece 114 to pivotally move to an unstressed width W2. This provides an intermediate headband unstressed width and would be suitable for slightly larger head sizes. Finally, Figure
30 5 depicts tab 162 at an outermost position, which allows the flexible headpiece to be pivotally moved to an unstressed width W3. This provides the widest headband unstressed width W3 for accommodating larger head sizes. The three unstressed

widths W1, W2, and W, for the flexible headpiece 114 may be suitable selected to cover the broadest range of head sizes.

In operation, a user slides the tab 162 to a position which provides a desired unstressed headband width.

5 Typically the unstressed width is slightly narrower than the user's head. The user then spreads the headband beyond its unstressed width by flexing the flexible headpiece 114 and slips the headband over his/her head. The tension provided by the stressed headband holds the headset in place.

10 The unstressed width of the above-described headband can advantageously be adjusted for various head sizes. Conventional headbands, as noted above, have only one unstressed width. With these conventional headbands, smaller heads are subject to less tension than larger heads. This often results in excessive tension on larger heads causing discomfort and too little tension on smaller heads making the headset prone to movement. The above headband alleviates these problems and
15 allows users with different sized heads to receive more comparable head tension.

As best illustrated in Figures 2A and 6-7, the illustrated headset assembly 100 further provides an electronics housing which may be readily removed from the headband 110 and, for example, attached to a hat of a user. The hat may, for example, be a baseball cap, a visor, and so forth. In the illustrated embodiment, an
20 exemplary clip member 140, is provided to facilitate the interchangeability of the electronics housing 120 between a hat and a headband. While, the invention is not so limited, the clip member 140 may, for example, be made of a substantially rigid plastic material, such as Nylon.

The exemplary clip member 140 includes an upper portion 141 for attaching
25 the clip member to the headband and hat, and a lower portion 148 to which the electronics housing 120 may be coupled. The clip member upper portion 141 includes two arms 142 and 144 which form a slot 146 therebetween. To attach the clip member 140 with the headband 110, a portion 118 of the support headpiece 112 is slidably received by the slot 146 of the clip member 140. The two arms 142
30 and 144 may be biased against one another with sufficient force to allow the clip member 140 to be slidably moved with respect to the support headpiece 112 while

retaining the clip member 140 at a desired position with respect to the support headpiece 112 under normal conditions. The clip member arms may be formed separately or from one integral molding.

As best shown in Figure 2A, the received portion 118 of the support headpiece 112 may be recessed with respect to an outer surface 119 of the support headpiece 112. The recess may be sufficiently deep to allow the outer surfaces 143 and 149 of the clip member arms 142 and 144 to be relatively flush with the outer surface 119 of the support headpiece 112. To secure the clip member 140 to the headband 110, the support headpiece 112 may include a tab which engages an opening in the clip member 140. The tab may be depressed for removing the clip member 140 from the headband 110. In an alternate embodiment, a depressable button may be provided on the clip member to secure the clip member 140 to the headband 110. The button may be depressed as the clip member 140 is slid downwardly against the headband to allow the clip member to be removed from the headband 110.

The clip member upper portion 141 may also be used to attach the electronics housing to a hat. For example, the clip member 140 may attach to a hat by slidably receiving a hat between the clip member arms 142 and 144. In an alternate embodiment, best illustrated in Figures 7A-7D, an adapter 700 is provided to attach the clip member 140 to a hat. The exemplary adapter 700 generally includes two legs 702 and 704, which are typically biased toward one another. The leg 704 includes an upper flange 706 having a slot 710 (as best shown in Figure 7B) and a lower flange 708. To attach the adapter 700 to the clip member 140, the slot 710 receives clip member arm 142. The adapter 700 is slid down the arm 142 until the lower flange 708 clips beneath the pad 130. A hat is attached to the adapter by sliding it between the adapter arms 702 and 704. The cap adapter 700 may, for example, be formed from a stainless steel.

The above described clip member advantageously allows the electronics housing to be interchangeably connected to a headband and a hat. The exemplary clip member is illustrative only. The present invention is not so limited. For example, a clip member having only one leg which is received by a slot formed by

the headband may be used to facilitate interchanging of an electronics housing. In this embodiment, a hat adapter could be employed to attach the clip member to a hat.

As illustrated in Figure 8, the exemplary headset assembly 100 further includes an electronics housing 120 which may be pivoted away from a user's ear. Generally the electronic housing 120 is pivotally coupled to the headband 110 using a hinge 110. The hinge 180 may, for example, include a variable friction pivot pin having a friction suitably selected to sufficiently hold electronic package 120 away from the user's ear while still allowing the electronics package 120 to be readily pivoted. This allows for the electronic package 120 to be positioned against the user's ear during periods of use and swung away from the user's ear during periods of nonuse or as desired to increase the comfort of the user.

In the exemplary embodiment, the electronics housing 120 is pivotally coupled with the headband 110 via the clip member 140. In particular, the electronics housing 120 is pivotally coupled with the clip member 140, for example, at the clip member extending portion 148. The clip member 140 is in turn attached to the headband 110, as discussed above. This allows the electronics housing 120 to be swung away from the user's ear when it is attached to a hat as well as a headband.

As best illustrated in Figures 2 and 9, the exemplary electronics housing 120 further includes a battery 900. A portion of the battery 900 may lie outside of the electronics housing when attached, as best shown in Figure 2. For example, a portion of the battery 900 may occupy the space between the speaker 128 and the electronics housing 120. By attaching the battery 900 to the electronics housing 120, the need for wiring between one end of the headset 100 and the electronics housing 120 is eliminated. In addition, the housing 120 may be detached from the headband 110 and used for communication. By disposing the battery 900 between the housing 120 and the speaker 128, otherwise unoccupied space is used and the width of the housing 120 may be reduced while still providing sufficient power for the electronics in the housing 120.

The battery 900 may be attached to the electronics housing 120 in a number of different manners. In the exemplary embodiment, the battery 900 is slidably received by a slot 902 in the electronics housing 120, as best illustrated in Figure 9. For securing the battery 900 in the slot 902, the received portion of the battery 900 and the slot 902 may have shapes or structural features which mate together to retain the battery 900. For example, the slot 902 may include flanges 904, on each side of the slot 902, which mate with corresponding recesses 906 on the battery 900. In the exemplary embodiment, a portion of a lower region of the battery 900 extends beyond an upper region of the battery 900 to form the battery recesses 906. A latch 908 may further be provided to secure the battery 900 in the axial direction of the slot 902. The latch 908 may, for example, be a spring loaded latch which is disposed upward while the battery 900 is inserted and which moves downward to engage a notch 910 in the battery 900 when the battery is fully inserted. To remove the battery 900, the latch 908 may be biased upwardly.

As noted above, the present invention is applicable to a wide variety of headset assemblies incorporating enhanced ergonomic features. While the illustrated embodiment incorporates a number of ergonomic features, the present invention is not so limited. Headset assemblies including any one or a combination of the features are covered by the present invention. Accordingly, the present invention should not be considered limited to the particular examples described above, but rather should be understood to cover all aspects of the invention as fairly set out in the attached claims. Various modifications as well as numerous equivalent structures to which the present invention may be applicable will be readily apparent to those of skill in the art to which the present invention is directed upon review of the present specification. The claims are intended to cover such modifications and structures.

WE CLAIM:

1. A headset assembly, comprising:
first headpiece,
5 second flexible headpiece pivotally coupled to the first headpiece; and
means for limiting the pivotal movement of the flexible headpiece with
respect to the first headpiece.
2. The headset assembly of claim 1, further including an electronics
10 housing coupled to the first headpiece.
3. The headset assembly of claim 2, wherein the electronics housing is
pivotally coupled to the first headpiece.
4. The headset assembly of claim 2, further including a clip member
15 removably coupled to the first headpiece and pivotally coupled to the electronics
housing.
5. The headset assembly of claim 4, further including a variable friction
20 pin for pivotally coupling the electronics housing to the clip member.
6. The headset assembly of claim 1, further including a pin for pivotally
coupling the flexible headpiece to the first headpiece.
7. The headset assembly of claim 1, wherein the limiting means includes
25 a movable surface for engaging the flexible headpiece and limiting the pivotal
movement thereof.
8. The headset assembly of claim 1, wherein the movable surface is
30 slidably mounted on the first headpiece for engaging the flexible headpiece at
multiple locations.

9. The headset assembly of claim 7, wherein the surface may be moved to at least three different positions.

5 10. The headset assembly of claim 1, wherein the first headpiece is substantially rigid.

11. The headset assembly of claim 1, wherein the electronics housing includes a speaker and a microphone.

10

12. A headset assembly, comprising:
a headband, and
an electronics housing pivotally coupled to the headband.

15 13. The headset assembly of claim 12, further including a variable friction pin for pivotally coupling the headband to the electronics housing.

14. The headset assembly of claim 12, further including a clip member coupled to the headband and pivotally coupled to the electronics housing using the
20 variable friction pin.

15. A headset assembly, comprising:
a headband;
a clip member removably coupled to the headband; and an electronics
25 housing coupled to the clip member; wherein the clip member and electronics housing may be removed from the headpiece and attached to a hat.

16. The headset assembly of claim 15, wherein the clip member includes two arms forming a slot for receiving a portion of the headpiece.

30

17. The headset assembly of claim 16, wherein the received portion of the headband is recessed with respect to an outer surface of the headband such that when received by the slot, the outer surface of the headband and an outer surface of the clip member are substantially flush.

5

18. The headset assembly of claim 15, wherein the electronics housing is pivotally coupled to the clip member, such that when the clip member is mounted on the headpiece, the electronics housing may pivot with respect to the headpiece.

10

19. The headset assembly of claim 15, further including an adapter capable of being coupled to the clip member, the adapter being configured to be removably mounted on the hat.

15

20. A headset assembly, comprising:
relatively rigid support headpiece;
a relatively flexible headpiece, pivotally coupled to the support headpiece;
and
a tab movably mounted on the support headpiece for engaging the flexible headpiece and limiting the pivotal movement thereof.

20

21. A headset assembly, comprising:
first headpiece having an end portion;
a second flexible headpiece pivotally coupled to the first headpiece, the second flexible headpiece having an end portion, the first headpiece end portion and second flexible headpiece end portion defining a width; and
means for adjusting the width without stressing the flexible headpiece.

25

22. An electronics housing for a headset assembly, comprising:

30

a speaker mounted on the electronics housing, the speaker and electronics housing defining a space therebetween; and

a battery for powering the electronics, the battery being at least partially disposed within the space between the speaker and electronics housing.

5 23. The electronics housing of claim 22, further including an open-sided slot for receiving and securing the battery to the housing, the slot being disposed proximate the speaker.

10 24. The electronics housing of claim 23, wherein the slot includes at least one flange and the battery includes a at least one recess, the at least one flange mating with the at least one recess to secure the battery to the electronics housing.

 25. The electronics housing of claim 22, further including a latch for retaining the battery to the electronics housing.

15 26. A battery for an electronics housing of a headset assembly, the battery comprising:


 a lower portion and an upper portion;


 wherein the lower portion is configured to mate with a slot of the electronics housing so that the battery may be securely attached.

20

 27. The battery of claim 26, wherein the lower portion extends beyond the upper portion thereby forming a recess, the recess being configured to mate with a flange of the electronics housing.


1/10






3/10

FIG. 2B




4/10

FIG. 3



5/10

FIG. 4



6/10

FIG. 5





FIG. 6



8/10

FIG. 7A




FIG. 7B




FIG. 7C






FIG. 7D



9/10


100

FIG. 8



10/10

FIG. 9



INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/07680

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H04R1/10

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,X	US 5 721 775 A (LEIFER) 24 February 1998	1,2,4,8, 10,11, 22,25
P,A	see column 1, line 50 - column 2, line 44	3,5-7,9, 12-21, 23,24, 26,27
	see column 3, line 36 - column 4, line 26 see column 4, line 48 - column 5, line 13 ---	
A	US 5 113 428 A (FITZGERALD) 12 May 1992 see column 2, line 37 - column 3, line 3 ---	1-27
A	US 5 117 464 A (JONES ET AL.) 26 May 1992 see column 2, line 40 - column 4, line 4 ---	1-21
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

*** Special categories of cited documents :**

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

25 September 1998

Date of mailing of the international search report

01/10/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.
Fax: (+31-70) 340-3016

Authorized officer

Zanti, P

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/07680

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	CH 244 196 A (ALBISWERK) 17 October 1947 see column 1, line 1-10 see column 3, line 30 - column 5, line 27 -----	1-3, 12, 13
A	EP 0 019 838 A (PEIKER) 10 December 1980 see page 4, line 16 - page 5, line 11 see page 10, line 12-20 -----	1, 2, 4, 12, 14-19

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 98/07680

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5721775 A	24-02-1998	US 5793865 A	11-08-1998
US 5113428 A	12-05-1992	NONE	
US 5117464 A	26-05-1992	NONE	
CH 244196 A		NONE	
EP 19838 A	10-12-1980	DE 2921434 A	27-11-1980
		AT 6012 T	15-02-1984